Cooled Incubator - Stainless Steel Interior And White Exterior

Series 3 200

LMS by Dulas Life Sciences

Reliable and accurate temperature control.

Our cooled incubators offer optimum temperature control from -10°C to +50°C with an average variation of 0.5°C and fluctuation of 0.1°C, or 0°C to +60°C upon request.

LMS has been producing scientific incubation products since 1979.



Key Features

Door lock
Preventing unauthorised access

Defrost
Automatic, with a manual override option built in

Fruit fly modification
Prevents corrosion caused by fruit flies

Self-evaporating drip tray
For additional temperature probes

Fan assisted air circulation
Keeping temperatures consistent

Heating / Cooling control
Optimising power usage when needed

Cooled Incubator - Stainless Steel Interior And White Exterior

	Series 3	
Standard	Model	200
	RJ45 interface for remote access (wired)	Yes
	Capacity (L)	227
	Material	Stove enameled mild steel
	Chamber material	Stainless steel
	Temperature range	-10°C to +50°C
	Accuracy	+0.5°C
	Height exterior (mm)	1550
	Width exterior (mm)	680
	Depth exterior (mm)	670
	Shelf size (mm)	510 x 390
	Weight (kg)	125
	Number of shelves	3
	Fruit fly modification	Yes
	Access porthole	Yes
Optional extras	Programmable controller	Yes
	Dual temperature control	Yes
	Double glazed door*	No
	Inner perspex door	Yes
	Extra shelves	Yes
	Fully programmable interior illumination	Yes
	Independent 24 hour / 7 day timer	Yes
	High / low AV alarm	Yes
	Integral chart recorder	Yes
	Internal 13A socket (EU/UK)	Yes
	Drying mode	Yes
	Corrosive conditions evaporator	Yes
	Pre-programming service	Yes