Cooled Incubator

# Series 4 1200

## Overview

Reliable and accurate temperature control.

Our cooled incubators offer optimum temperature control from -10°C to +50°C with an average variation of 0.5°C and fluctuation of 0.1°C, or 0°C to +60°C upon request.

Built on a legacy of expertise since 1979.



## Key Features

### Door Lock
Preventing unauthorised access

### Defrost
Automatic, with a manual override option built in

### Fruit Fly Modification
Prevents corrosion caused by fruit fly

### Self-Evaporating Condensate Drip Tray
Eliminating the pooling of moisture

### Fan Assisted Air Circulation
Keeping temperatures consistent

### Flexible Temperature
-10°C to 50°C as standard, 0°C to 60°C on request (glass door 0-40°C)

# Series 4 1200 - Product Specification

| Series 4 1200 | |
|---|---|
| Model | 1200 |
| Capacity (Litres) | 1200 |
| Material | Stainless Steel |
| Chamber Material | Stainless Steel |
| Temperature Range | -10°C to +50°C |
| Accuracy | ±0.5°C |
| Height Exterior (mm) | 2080 |
| Width Exterior (mm) | 1500 |
| Depth Exterior (mm) | 900 |
| Shelf Size (mm) | 530 x 550 |
| Weight (kg) | 235 |
| Number of Shelves | 10 |
| Access Porthole | Yes |
| Optional Extras | |
| Programmable Controller | Yes |
| Dual Temperature Control | Yes |
| Double Glazed Door | Yes |
| Inner Perspex Door | Yes |
| Extra Shelves | Yes |
| Fully Programmable Interior Illumination | Yes |
| Independent 24 Hour / 7 Day Timer | Yes |
| High / Low A/V Alarm | Yes (audible only) |
| Integral Chart Recorder | Yes |
| Internal 13A Socket (EU/UK) | Yes |
| Drying Mode | Yes |
| Door Vents | Yes |
| LED Shelf Lighting | No |
| Corrosive Conditions Evaporator | Yes |
| Options for Models with Fully-Programmable Controller | |
| Pre-Programming Service | Yes |