Cooled Incubator

410 XAL



Overview

Reliable and accurate temperature control.

Our cooled incubators offer optimum temperature control from -10°C to +50°C with an average variation of 0.5°C and fluctuation of 0.1°C, or 0°C to +60°C upon request.

Built on a legacy of expertise since 1979.

Key Features

Door Lock
Preventing unauthorised access

Defrost
Automatic, with a manual override option built in

Fruit Fly Modification
Prevents corrosion caused by fruit fly

Self-Evaporating Condensate Drip Tray
Eliminating the pooling of moisture

Fan Assisted Air Circulation
Keeping temperatures consistent

Flexible Temperature
-10°C to 50°C as standard, 0°C to 60°C on request (glass door 0-40°C)

410 XAL - Product Specification

XAL	
Model	XAL
Capacity (Litres)	450
Material	Stove Enamelled Mild Steel
Chamber Material	Pre Coated Aluminium
Temperature Range	-10°C to +50°C
Accuracy	±0.5°C
Height Exterior (mm)	1880
Width Exterior (mm)	690
Depth Exterior (mm)	920
Shelf Size (mm)	530x600
Weight (kg)	140
Number of Shelves	4
Access Porthole	Yes
Optional Extras	
Programmable Controller	No
Dual Temperature Control	Yes (as standard)
Double Glazed Door	No
Inner Perspex Door	Yes
Extra Shelves	Yes
Fully Programmable Interior Illumination	No
Independent 24 Hour / 7 Day Timer	Yes (as standard)
High / Low A/V Alarm	Yes (as standard)
Integral Chart Recorder	Yes
Internal 13A Socket (EU/UK)	Yes
Drying Mode	Yes
Door Vents	Yes (as standard)
LED Shelf Lighting	Yes (as standard)
Corrosive Conditions Evaporator	Yes
Options for Models with Fully-Programmable Controller	
Pre-Programming Service	Yes