

Pharmacy Refrigerator

— HYC-940



Six Alarm Functions

High/low temperature, remote alarm, power failure, sensor error, low battery, door ajar



Air Cooling, Auto Defrost

Better cabinet temperature uniformity, auto defrost



Adjustable Shelves

The shelves are adjustable to any height to fulfill different requirements



Heated Double Pane Glass Door

Clear display of stored products without condensation at 32°C and 85% relative humidity condition



Self Closing Door

Energy conserving, maintains temperature uniformity to protect valuable samples

Ergonomic Design



High Accuracy
Temperature Control



Interior
LED



Lockable
Design

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: +86-0532-88935593
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



@haierbiomedicalint



Haier Biomedical
International

Specifications



Technical Data

Cabinet Type	Upright, double glass door
Climate Class	N
Cooling Type	Forced air cooling
Defrost Mode	Auto
Refrigerant	HC
Noise((dB(A))	43

Performance

Temp Range(°C)	2~8
----------------	-----

Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply(V/Hz)	220~240/50/60	115/60
Power(W)	700	850
Electrical Current(A)	3.5	7.5

Dimensions

Capacity(L/Cu.Ft)	890/31.4
Net/Gross Weight(approx)	227/279(kg) 500.4/615.1(lbs)
Interior Dimensions(W*D*H)	1030*590*1425(mm) 40.6*23.2*56.1(in)
Exterior Dimensions(W*D*H)	1130*755*1980(mm) 44.5*29.7*78.0(in)
Packing Dimensions(W*D*H)	1250*850*2130(mm) 49.2*33.5*83.9(in)
Container Load(20'/40'/40'H)	8/18/18



Functions

High/Low Temp	Y
Remote Alarm	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
Door Ajar	Y

Accessories

Caster	Y
Foot	Y
Porthole	Y
Shelves/Basket	12/-
Temperature Recorder	Optional
USB Interface	Optional

Others

Certificate	CE	UL
-------------	----	----